

LEISTUNGSERKLÄRUNG

Nr. NLD0001-0005-06 (DE)

1. Eindeutiger Kenncode des Produkttyps:

ISOCONFORT 35 BEL	MW-EN-13162-T2-WS
COMFI UNI G3	MW-EN-13162-T2-WS
MUPAN	MW-EN-13162-T5-WS-WL(P)
MUPAN 35	MW-EN-13162-T5-WS-WL(P)
RENOPAN	MW-EN-13162-T5-WS-WL(P)
HEAT SHIELD	MW-EN-13162-T2-WS
PAN NO700	MW-EN-13162-T4
EASYPAN	MW-EN-13162-T5-WS-WL(P)-AFr10
SYSTEMROLL 700	MW-EN-13162-T2
SYSTEMROLL 700 G3	MW-EN-13162-T3
TIMBERFRAME 35	MW-EN-13162-T3
SONEBEL 113	MW-EN-13162-T4-AFr10
PARTYWALL BEL	MW-EN-13162-T3
ROLLISOL PLUS 35	MW-EN-13162-T3
CLADIPAN 35 (BLACK)	MW-EN-13162-T4-WS

2. Kennzeichen zur Identifikation des Bauprodukts:

Einzighartes Produkt Namen und Code (wie unter Punkt 1 genannten) (Siehe auch Etikett für die Rückverfolgbarkeit)

3. Vorgesehener Verwendungszweck (gemäß der harmonisierten technischen Spezifikation):

Wärmedämmung für die Gebäudeausrüstung (THiB)

4. Name, eingetragener Handelsname und Kontaktanschrift des Herstellers:

SAINT-GOBAIN ISOVER
Parallelweg 20, 4878 AH, Etten-Leur, Nederland

5. Name und Kontaktanschrift des Bevollmächtigten:

Nicht anwendbar

6. System(e) zur Bewertung und Überprüfung der Leistungsbeständigkeit des Bauprodukts:

AVCP System 1 für Brandverhalten A1 – A3 & AVCP System 3 für anderen Eigenschaften
AVCP System 4 für Brandverhalten F & AVCP System 3 für anderen Eigenschaften

7. Im Falle der Leistungserklärung, die ein Bauprodukt betrifft, das von einer harmonisierten Norm erfasst wird:

KIWA (Notifizierten Stelle n° 0620) hat Feststellung des Produkttyps anhand einer Typprüfung (einschließlich Probenahme); Erstinspektion des Werks und der werkseigenen Produktionskontrolle; laufende Überwachung, Bewertung und Evaluierung der werkseigenen Produktionskontrolle; nach dem System 1

BDA (Notifizierten Stelle n°1640) & KIWA (Notifizierten Stelle n° 0620),

hat stellt anhand einer Typprüfung (auf der Grundlage der vom Hersteller gezogenen Stichprobe), den Produkttyp fest, nach dem System 3 vorgenommen.

8. Im Falle der Leistungserklärung, die ein Bauprodukt betrifft, für das eine Europäische Technische Bewertung ausgestellt worden ist:

Nicht anwendbar

9. Erklärte Leistung:

Alle Eigenschaften in der nachstehenden Tabelle aufgeführt sind in der harmonisierten Norm **EN 13162:2012+A1:2015** festgelegt.

Essential characteristics Requirement clauses in the european standard	ISOCONFORT 35 BEL	COMFI UNI G3
Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K	
Thickness (4.2.3)	T2	T2
Reaction to Fire (4.2.6)	A2-s1,do	F (>160 mm)
Water absorption (4.3.7.1)	< 1 kg / m ²	
Water absorption (4.3.7.2)	NPD	
Water vapour transmission (4.3.8)	NPD	
Release of dangerous substances (4.3.13)	NPD	
Sound absorption (4.3.11)	NPD	
Dynamic stiffness (4.3.9)	NPD	
Thickness (4.3.10.2)	NPD	
Compressability (4.3.10.4)	NPD	
Air Flow resistivity (4.3.12)	NPD	
Air Flow resistivity (4.3.12)	NPD	
Continuous glowing combustion (4.3.15)	NPD	
Compressive stress or compressive strength (4.3.3)	NPD	
Point load (4.3.5)	NPD	
Durability characteristics (4.2.7) ^{a,b}	NPD	
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	
Durability characteristics (4.2.7) ^d	NPD	
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	
Compressive creep (4.3.6)	NPD	
CE Designation code	MW-EN13162-T2-WS	MW-EN13162-T2-WS
CE certificatenumber	48456	48456

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics Requirement clauses in the european standard	MUPAN MUPAN 35 RENOPAN	HEAT SHIELD
Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K	
Thickness (4.2.3)	T5	T2
Reaction to Fire (4.2.6)	A1	F (> 140 mm)
Water absorption (4.3.7.1)	< 1 kg / m ²	< 1 kg / m ²
Water absorption (4.3.7.2)	< 3 kg / m ²	NPD
Water vapour transmission (4.3.8)	NPD	NPD
Release of dangerous substances (4.3.13)	NPD	NPD
Sound absorption (4.3.11)	NPD	NPD
Dynamic stiffness (4.3.9)	NPD	NPD
Thickness (4.3.10.2)	NPD	NPD
Compressability (4.3.10.4)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive stress or compressive strength (4.3.3)	NPD	NPD
Point load (4.3.5)	NPD	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
Durability characteristics (4.2.7) ^d	NPD	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
Compressive creep (4.3.6)	NPD	NPD
CE Designation code	MW-EN13162-T5-WS-WL(P)	MW-EN13162-T2-WS
CE certificatenumber	41532	48456

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics Requirement clauses in the european standard	ROLLISOL PLUS 35	PAN N0700
Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K	
Thickness (4.2.3)	T3	T4
Reaction to Fire (4.2.6)	F	A1
Water absorption (4.3.7.1)	NPD	NPD
Water absorption (4.3.7.2)	NPD	NPD
Water vapour transmission (4.3.8)	NPD	NPD
Release of dangerous substances (4.3.13)	NPD	NPD
Sound absorption (4.3.11)	NPD	NPD
Dynamic stiffness (4.3.9)	NPD	NPD
Thickness (4.3.10.2)	NPD	NPD
Compressability (4.3.10.4)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive stress or compressive strength (4.3.3)	NPD	NPD
Point load (4.3.5)	NPD	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
Durability characteristics (4.2.7) ^d	NPD	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
Compressive creep (4.3.6)	NPD	NPD
CE Designation code	MW-EN13162-T3	MW-EN13162-T4
CE certificatenumber	SYSTEM 3	41520

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics Requirement clauses in the european standard	SONEBEL 113	EASYPAN
Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K	
Thickness (4.2.3)	T4	T5
Reaction to Fire (4.2.6)	A1	A1
Water absorption (4.3.7.1)	NPD	< 1 kg / m ²
Water absorption (4.3.7.2)	NPD	< 3 kg / m ²
Water vapour transmission (4.3.8)	NPD	NPD
Release of dangerous substances (4.3.13)	NPD	NPD
Sound absorption (4.3.11)	NPD	NPD
Dynamic stiffness (4.3.9)	NPD	NPD
Thickness (4.3.10.2)	NPD	NPD
Compressability (4.3.10.4)	NPD	NPD
Air Flow resistivity (4.3.12)	10 kPa.s/m ²	10 kPa.s/m ²
Air Flow resistivity (4.3.12)	10 kPa.s/m ²	10 kPa.s/m ²
Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive stress or compressive strength (4.3.3)	NPD	NPD
Point load (4.3.5)	NPD	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
Durability characteristics (4.2.7) ^d	NPD	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
Compressive creep (4.3.6)	NPD	NPD
CE Designation code	MW-EN13162-T4-AFr10	MW-EN13162-T5-WS-WL(P)-AFr10
CE certificatenumber	41534	41532

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics Requirement clauses in the european standard	SYSTEMROLL 700	SYSTEMROLL 700 G3 TIMBERFRAME 35
Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K	
Thickness (4.2.3)	T2	T3
Reaction to Fire (4.2.6)	A1	F (> 190 mm)
Water absorption (4.3.7.1)	NPD	NPD
Water absorption (4.3.7.2)	NPD	NPD
Water vapour transmission (4.3.8)	NPD	NPD
Release of dangerous substances (4.3.13)	NPD	NPD
Sound absorption (4.3.11)	NPD	NPD
Dynamic stiffness (4.3.9)	NPD	NPD
Thickness (4.3.10.2)	NPD	NPD
Compressability (4.3.10.4)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive stress or compressive strength (4.3.3)	NPD	NPD
Point load (4.3.5)	NPD	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
Durability characteristics (4.2.7) ^d	NPD	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
Compressive creep (4.3.6)	NPD	NPD
CE Designation code	MW-EN13162-T3	MW-EN13162-T3
CE certificatenummer	41520	41520

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics	Requirement clauses in the european standard	Cladipan 35	Cladipan 35 BLACK
Thermal resistance	Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K	
	Thickness (4.2.3)	T4	T4
Reaction to fire Euroclass characteristics	Reaction to Fire (4.2.4)	A2,s1-d0	E
Water permeability	Water absorption (4.3.1)	< 1 kg / m ²	< 1 kg / m ²
	Water absorption (4.3.2)	NPD	NPD
Water Vapour permeability	Water vapour transmissivity (4.3.3)	NPD	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances (4.3.13)	NPD	NPD
Acoustic absorption index	Sound absorption (4.3.11)	NPD	NPD
Impact Noise transmission index (for floors)	Dynamic stiffness (4.3.10.1)	NPD	NPD
	Thickness (4.3.10.2)	NPD	NPD
	Compressability (4.3.10.3)	NPD	NPD
	Air Flow resistivity (4.3.10.4)	NPD	NPD
Direct Airborne sound insulation index	Air Flow resistivity (4.3.10.4)	NPD	NPD
Continuous glowing combustion	Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive strength	Compressive stress or compressive strength (4.3.3)	NPD	NPD
	Point load (4.3.5)	NPD	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics (4.3.16)	NPD	NPD
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
	Durability characteristics (4.3.16)	NPD	NPD
Tensile/flexural strength	Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
durability of compressive strength against ageing/degradation	Compressive creep (4.3.6)	NPD	NPD
CE Designation code		MW-EN13162-T4-WS	MW-EN13162-T4-WS
CE certificatenummer		85444	DoP:0001-0005-06NL

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics Requirement clauses in the european standard	PARTY-WALL BEL
Thermal resistance and thermal conductivity (4.2.1)	0,035 mW/m.K
Thickness (4.2.3)	T3
Reaction to Fire (4.2.6)	A2-s1,d0
Water absorption (4.3.7.1)	< 1 kg / m ²
Water absorption (4.3.7.2)	NPD
Water vapour transmission (4.3.8)	NPD
Release of dangerous substances (4.3.13)	NPD
Sound absorption (4.3.11)	NPD
Dynamic stiffness (4.3.9)	NPD
Thickness (4.3.10.2)	NPD
Compressability (4.3.10.4)	NPD
Air Flow resistivity (4.3.12)	NPD
Air Flow resistivity (4.3.12)	NPD
Continuous glowing combustion (4.3.15)	NPD
Compressive stress or compressive strength (4.3.3)	NPD
Point load (4.3.5)	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD
Durability characteristics (4.2.7) ^d	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD
Compressive creep (4.3.6)	NPD
CE Designation code	MW-EN13162-T3-WS
CE certificatenummer	41530

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

10. Die Leistung des Produkts gemäß den Nummern 1 und 2 entspricht der erklärten Leistung nach Nummer 9.

Verantwortlich für die Erstellung dieser Leistungserklärung ist allein der Hersteller gemäß Nummer 4.

Unterzeichnet für den Hersteller und im Namen des Herstellers von:

Mark Rippens
Plant Manager Saint-Gobain Isover



Datum: 20-04-2022

Etten-Leur